

# A21 LED 16.5W HO 277V TITANIUM LED SERIES



PRO



Optional Lamp Extender

16.5W REPLACES




125W  
Inc.

70% Energy Savings

- Direct line voltage 120-277V - Not compatible with ballasts
- Compact form factor - Ideal for bollards & post tops
- Exceptional efficacy 121 LPW in Cool White
- Frosted diffuser maintains low glare
- Optional lamp extender available for use in larger fixtures
- Suitable for use in totally enclosed fixtures



40,000 H



UNIVERSAL



EFFICACY



WARRANTY



CRI (Ra)



ENCLOSED\*\*



## A21 LED PRODUCT FEATURES


Suitable for Enclosed Fixtures



This A21 LED lamp replaces a 125W Inc. and is suitable for use in enclosed fixtures. Its high lumen output and exceptional efficacy make it an ideal choice for bollard, post top and other outdoor applications. An optional lamp extender is also available for use in larger fixtures.

## Omnidirectional Lighting

This A21 LED emits 330° of uniform light and meets ENERGY STAR requirements. Its compact form factor and omnidirectional output provides a fuller distribution than other LED lamps.



# A21 LED 16.5W HO 277V TITANIUM LED SERIES



## APPLICATIONS

### General Lighting



### Bollard Lighting



### Post Top Lighting



## SPECIFICATIONS

Product Model	58238 16.5A21/830/277V	58239 16.5A21/840/277V	58240 16.5A21/850/277V
Type	A21	A21	A21
Base	E26	E26	E26
Power (W)	16.5	16.5	16.5
Voltage - Frequency	120-277V 50/60Hz	120-277V 50/60Hz	120-277V 50/60Hz
Color Temp. (ANSI)	Warm White 3000K	Cool White 4000K	Daylight 5000K
CRI (Ra) (typ.)	82	82	82
Typical lumens (lm)	2000	2000	2050
Efficacy (LPW)	121	121	124
Beam Angle	330°	330°	330°
Dimmable	No	No	No
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	40,000	40,000	40,000
Dia. x MOL	2.55"x5.00" (65x127mm)	2.55"x5.00" (65x127mm)	2.55"x5.00" (65x127mm)
Weight (lb. / g)	0.50lb. / 227g	0.50lb. / 227g	0.50lb. / 227g

\* Suitable for use in totally enclosed fixtures

\*\* Suitable for damp locations. Not for use where directly exposed to weather or water

Ref.#: DS180-A21-16.5W-277V-140818